

Cable ties with steel tongue as standard

<p>Characteristics</p> <ul style="list-style-type: none"> • Standard (Polyamide 6.6), to cover most indoor applications • Four lengths and 2 typical widths with a tensile strength up to 120LBS(54.4kgs), the design of the head optimizes grip, the hardened stainless steel teeth ensures extremely high mechanical strength and optimal resistance to corrosion. • Packaging: OEM bulk quantities in plastic bags • Also be available in small bags with Euroslot and in workbench boxes 	<p>Technical information</p> <ul style="list-style-type: none"> • Material - Molding: UL approved Polyamide 6.6 Material - Locking bar: 304 grade stainless steel • Temperature range: -20°C to +85°C (-4°F to 185°F) • Min. Installation Temp.: -20°C (-4°F) • Color: Natural, black, customized color • Flammability rating: UL 94V-2 • Other properties: Halogen free, Silicone free
---	---



Product code	Length L		Width w		Max Bundle		Min.Tensile Strength		Pack quantity
	[mm]	[in]	[mm]	[in]	[mm]	[in]	[kgs]	[lbs]	[pcs]
Standard Ties (50 lb., 22.2 kg)									
GC-200ST	200	7.9	4.8	0.19	50	2.0	22.2	50	100/1000
GC-300ST	300	11.8	4.8	0.19	76	3.0	22.2	50	100/1000
Heavy Duty Ties (120 lb., 54.4 kg)									
GC-300HD	300	11.8	9.4	0.37	76	3.0	54.4	120	100
GC-370HD	370	14.6	9.4	0.37	102	4.0	54.4	120	100

Drawing GC-200ST

